


FDX 2

2 wheels - 2 ruote



FDX 2 10/150 - VRX

GENERAL FEATURES - CARATTERISTICHE GENERALI

- Loncin G 200 F Engine
- **Comet VRX 3 axial piston pump with brass pump head**
- Readily serviceable suction filter
- Professional unloader valve
- No engine oil safety device (oil-alert)
- **Motore Loncin G 200 F**
- **Pompa Comet a 3 pistoni assiali VRX, con testata in ottone**
- Filtro aspirazione ispezionabile
- Valvola regolazione professionale
- Dispositivo di sicurezza mancanza olio motore (oil-alert)
- **Uso semiprofessionale**

FDX 2 12/200 - BXD

GENERAL FEATURES - CARATTERISTICHE GENERALI

- Loncin G 200 F Engine
- **Comet BXD self-priming pump with 3 axial integral ceramic pistons and brass pump head**
- Regulated low-pressure detergent suction
- Readily serviceable suction filter
- Professional unloader valve
- No engine oil safety device (oil-alert)
- **Motore Loncin G 200 F**
- **Pompa Comet BXD autoadescente con 3 pistoni assiali in ceramica e testata in ottone**
- Aspirazione detergente in bassa pressione con regolazione
- Filtro aspirazione ispezionabile
- Valvola regolazione professionale
- Dispositivo di sicurezza mancanza olio motore (oil-alert)
- **Uso semiprofessionale**

FDX 2 - BXD / AXD

GENERAL FEATURES - CARATTERISTICHE GENERALI

- Honda GP or GX series engine
- **No engine-oil safety device (oil-alert)**
- **Comet BXD-AXD self-priming pumps with 3 axial ceramic pistons and brass pump head**
- Regulated low-pressure detergent suction
- Readily serviceable suction filter
- Professional unloader valve
- No engine oil safety device (oil-alert)
- **Motore Honda serie GP o GX**
- **Dispositivo di Sicurezza mancanza olio motore**
- **Pompe Comet BXD-AXD autoadescenti con 3 pistoni assiali in ceramica e testata in ottone**
- Aspirazione detergente in bassa pressione con regolazione
- Filtro aspirazione ispezionabile
- Valvola regolazione professionale
- Dispositivo di sicurezza mancanza olio motore (oil-alert)
- **Uso semiprofessionale**

FDX 2 - BWD-K / ZWD / ZWD-K

GENERAL FEATURES - CARATTERISTICHE GENERALI

- Honda GX series engine
- **No engine-oil safety device (oil-alert)**
- **Comet BWD, ZWD, ZWD-K self-priming triplex pumps, 3 ceramic pistons, brass pump head, bronze conrods**
- Regulated low-pressure detergent suction
- Readily serviceable suction filter
- Professional unloader valve
- No engine oil safety device (oil-alert)
- **Motore Honda serie GX**
- **Dispositivo di Sicurezza mancanza olio motore**
- **Pompe Comet BWD, ZWD, ZWD-K triplex autoadescenti, 3 pistoni in ceramica, testata ottone, bielle in bronzo**
- Aspirazione detergente in bassa pressione con regolazione
- Filtro aspirazione ispezionabile
- Valvola regolazione professionale
- Dispositivo di sicurezza mancanza olio motore (oil-alert)
- **Uso semiprofessionale**

- Easy to handle up and down steps and over uneven ground
- *Facilità di movimento su gradini e fondi sconnessi*



- Well balanced for easy handling
- *Estrema maneggevolezza grazie alla favorevole posizione del baricentro*



VRX



BXD



AXD



BWD-K



ZWD-K



ZWD

CODE CODICE	MODELS MODELLI	PUMP POMPE						
			bar	MPa				
9020 1155	FDX 2 10/150 - Loncin G200 F	VRX	150	15	540	6,0	27	67 x 55 x 89
9020 1156	FDX 2 12/200 - Loncin G200 F	BXD	200	20	720	6,0	30	67 x 55 x 89
9020 1315	FDX 2 13/150 - Honda GP160	BXD	150	15	780	5,0	30	67 x 55 x 89
9020 1316	FDX 2 12/200 - Honda GP200	BXD	200	20	720	6,0	30	67 x 55 x 89
9020 1304	FDX 2 14/200 - Honda GX270	AXD	200	20	840	9,0	40	67 x 55 x 89
9020 1317	FDX 2 12/140 - Honda GP160	BWD-K	140	14	720	5,5	30	67 x 55 x 89
9020 1306	FDX 2 13/180 - Honda GX200	BWD-K	180	18	780	6,0	34	67 x 55 x 89
9020 1308	FDX 2 16/210 - Honda GX340	ZWD-K	210	21	960	11,0	48	67 x 55 x 89
9020 1309	FDX 2 16/250 - Honda GX390	ZWD	250	25	960	13,0	50	67 x 55 x 89
9020 1310	FDX 2 15/270 - Honda GX390	ZWD-K	270	27	900	13,0	50	67 x 55 x 89



STANDARD ACCESSORIES › DOTAZIONE STANDARD

FDX2 Loncin

	Gun GC 251 with protection <i>Pistola con protezione GC 251</i>
	Bent lance with detergent head, without nozzle <i>Lancia angolata con testina detergente, senza ugello</i>
	Fan shape nozzle 15°, 1/4" MEG connection <i>Ugello con getto a lama 15°, attacco 1/4" MEG</i>
	8 m rubber delivery hose kit <i>Kit tubo gomma mandata 8 m</i>
	Foam lance (only for 10/150 model) <i>Lancia schiumogena (solo per modello 10/150)</i>

FDX2 Honda

	GH 301 gun with Swivel <i>Pistola GH 301 con Swivel</i>
	Bent lance with detergent head, without nozzle <i>Lancia angolata con testina detergente, senza ugello</i>
	Fan shape nozzle 25°, 1/4" MEG connection <i>Ugello con getto a lama 25°, attacco 1/4" MEG</i>
	10 m rubber delivery hose kit (8 m for 13/150 - 12/200 - 12/140 models) <i>Kit tubo gomma mandata 10 m (8 m per modelli 13/150 - 12/200 - 12/140)</i>